


UP. 02. SFTR

- 45° Reinforced elbow
- Female solvent socket & BSP female thread
- Metric series

- Coude 45° renforcé
- Femelle à coller et femelle à visser BSP
- Série métrique

- Gomito 45° rinforzato
- Incollaggio femmina e filetto femmina BSP
- Serie metrica

- Übergangswinkel 45° verstärkt
- Klebemuffe/Innengewinde BSP
- Metrische Serie



D x G	CODE	REF.	DN	PN	L	Z	E
20 x 1/2"	01774	05 02 820	15	16	16	5	28
25 x 3/4"	01775	05 02 825	20	16	19	6	34
32 x 1"	01776	05 02 832	25	16	22	8	43
40 x 1 1/4"	01777	05 02 840	32	16	26	10	54
50 x 1 1/2"	01778	05 02 850	40	16	31	12	63
63 x 2"	01779	05 02 863	50	16	38	14	78


UP. 02. FT

- 45° Elbow
- BSP female thread

- Coude 45°
- Femelle à visser BSP

- Gomito 45°
- Filetto femmina BSP

- Winkel 45°
- Innengew. BSP/Innengew. BSP



G	CODE	REF.	DN	PN	L	Z	E
1/2"	01768	05 02 620	15	10	16	5	28
3/4"	01769	05 02 625	20	10	19	6	34
1"	01770	05 02 632	25	10	22	8	43
1 1/4"	01771	05 02 640	32	10	26	10	54
1 1/2"	01772	05 02 650	40	10	31	12	63
2"	01773	05 02 663	50	10	38	14	78
2 1/2"	22590	05 02 675	65	10	30	32	89
3"	22591	05 02 690	80	10	34	39	106
4"	22592	05 02 710	100	10	40	47	129


UP. 30. SFG

- 45° Reducing elbow
- Female and male solvent socket
- Metric series

- Coude 45° rédiut
- Femelle et mâle à coller
- Série métrique

- Gomito 45° ridotto
- Incollaggio femmina e maschio
- Serie metrica

- Reduzierwinkel 45°
- Klebemuffe/klebestutzen
- Metrische Serie



D x D - d	CODE	REF.	DN	PN	L	L ₁	E
50 x 50 - 40	02241	05 30 050	32	16	31	26	61
63 x 63 - 50	02242	05 30 063	40	16	38	31	76